

Safety Data Sheet RESFOAM 1K-M

Safety Data Sheet dated 7/9/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: RESFOAM 1K-M

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Polyurethane foam

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI S.p.A. - Via Cafiero 22 - Milan - ITALY

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Acute Tox. 4, Harmful if inhaled.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Danger, Resp. Sens. 1, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Carc. 2, Suspected of causing cancer.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Safety Data Sheet

RESFOAM 1K-M

Danger

Hazard Statements:

- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

- P201 Obtain special instructions before use.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special Provisions:

- EUH204 Contains isocyanates. May produce an allergic reaction.

Contents:

- diphenylmethane-4,4'-diisocyanate;
- diphenylmethanediisocyanate isomers and homologues

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

- >= 50% - < 75% diphenylmethane-4,4'-diisocyanate;
REACH No.: 01-2119457014-47-XXXX, Index number: 615-005-00-9, CAS: 101-68-8, EC: 202-966-0
 - ⚠ 3.1/4/Inhal Acute Tox. 4 H332
 - ⚠ 3.3/2 Eye Irrit. 2 H319
 - ⚠ 3.8/3 STOT SE 3 H335
 - ⚠ 3.2/2 Skin Irrit. 2 H315
 - ⚠ 3.4.1/1-1A-1B Resp. Sens. 1,1A,1B H334
 - ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
 - ⚠ 3.9/2 STOT RE 2 H373
 - ⚠ 3.6/2 Carc. 2 H351
- >= 20% - < 25% diphenylmethanediisocyanate isomers and homologues
Index number: 615-005-00-9, CAS: 9016-87-9, EC: 618-498-9
 - ⚠ 3.1/4/Inhal Acute Tox. 4 H332
 - ⚠ 3.3/2 Eye Irrit. 2 H319
 - ⚠ 3.8/3 STOT SE 3 H335

Safety Data Sheet

RESFOAM 1K-M

- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.4.1/1-1A-1B Resp. Sens. 1,1A,1B H334
- ⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317
- ⚠ 3.9/2 STOT RE 2 H373
- ⚠ 3.6/2 Carc. 2 H351

>= 20% - < 25% propylene carbonate

REACH No.: 01-2119537232-48-xxxx, Index number: 607-194-00-1, CAS: 108-32-7, EC: 203-572-1

- ⚠ 3.3/2 Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

Wash immediately with water for at least 10 minutes.

In case of Ingestion:

Do NOT induce vomiting.

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

A suspension of activated charcoal in water, or petroleum jelly may be administered.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

The product is harmful following acute exposure to it and poses a serious health threat if inhaled.

If brought into contact with the eyes, the product causes irritation that may last for over 24h, if inhaled, it causes irritation to the airways, and if brought into contact with the skin it causes significant inflammation with erythema, scabs, and oedema

The product may present a risk of carcinogenesis.

If inhaled, the product may cause sensitisation of the airways, and if brought into contact with the skin it may cause sensitisation of the skin.

This product is harmful: serious harm (functional disorders or significant morphological changes that are toxicology-related) may be caused by repeated or prolonged exposure to the product by inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

Safety Data Sheet

RESFOAM 1K-M

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
Suitable extinguishing media:
None in particular.
Water.
Extinguishing media which must not be used for safety reasons:
None in particular.
- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Limit leakages with earth or sand.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Rapidly recover the product, wearing protective clothing.
Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.
Retain contaminated washing water and dispose it.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.
Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)
- 7.2. Conditions for safe storage, including any incompatibilities
Always keep the containers tightly closed.

Safety Data Sheet

RESFOAM 1K-M

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

diphenylmethane-4,4'-diisocyanate; - CAS: 101-68-8

SUVA - LTE mg/m³: 0.02 mg/m³ - STE mg/m³: 0.02 mg/m³

NDS - LTE mg/m³: 0.03 mg/m³

NDSP - LTE mg/m³: 0.09 mg/m³

ACGIH - LTE mg/m³(8h): 0.005 ppm - Notes: Resp sens

diphenylmethanediisocyanate isomers and homologues - CAS: 9016-87-9

ACGIH - LTE mg/m³: 0.05 ppm

SUVA - LTE mg/m³: 0.02 mg/m³ - STE mg/m³: 0.02 mg/m³

DNEL Exposure Limit Values

diphenylmethane-4,4'-diisocyanate; - CAS: 101-68-8

Worker Industry: 50 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 0.1 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 0.1 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 0.05 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 0.05 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 25 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 0.05 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 20 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 0.05 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 0.025 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 0.025 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

propylene carbonate - CAS: 108-32-7

Worker Industry: 50 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 20 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 176 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 25 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 43.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 25 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Safety Data Sheet

RESFOAM 1K-M

PNEC Exposure Limit Values

diphenylmethane-4,4'-diisocyanate; - CAS: 101-68-8

Target: Fresh Water - Value: 1 mg/l

Target: Marine water - Value: 0.1 mg/l

Target: Soil (agricultural) - Value: 1 mg/kg

Target: Microorganisms in sewage treatments - Value: 1 mg/l

propylene carbonate - CAS: 108-32-7

Target: Marine water - Value: 0.09 mg/l

Target: Fresh Water - Value: 0.09 mg/l

Target: Microorganisms in sewage treatments - Value: 7400 mg/l

Target: Soil (agricultural) - Value: 0.81 mg/kg

8.2. Exposure controls

Eye protection:

Safety goggles.

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Respiratory protection:

Use adequate protective respiratory equipment.

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

In case of insufficient ventilation use mask with AK2 filters (EN 141).

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	brown
Odour:	typical
Odour threshold:	N.A.
pH:	7
Melting point / freezing point:	<- 20 °C
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	> 130 °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.

Safety Data Sheet

RESFOAM 1K-M

Relative density:	1,115 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	insoluble
Solubility in oil:	soluble
Viscosity:	== mPa.s (23°C)
Auto-ignition temperature:	N.A.
Explosion limits(by volume):	N.A.
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth, alloys in powder or vapours) and powerful reducing agents.

It may generate toxic gases on contact with oxidising mineral acids, and powerful oxidising agents.

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

It releases carbon dioxide in contact with water

It polymerises on heating

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion: Yes

Inhalation: Yes

Contact: No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

The following tests refer to a mixture with a similar composition

Toxicological information on main components of the mixture:

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

diphenylmethane-4,4'-diisocyanate; - CAS: 101-68-8

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Safety Data Sheet

RESFOAM 1K-M

Test: LD50 - Route: Skin - Species: Rabbit > 9400 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 0.49 mg/l - Duration: 4h
Test: LC50 - Route: Inhalation - Species: Rat = 2.24 mg/l - Duration: 1h
diphenylmethanediisocyanate isomers and homologues - CAS: 9016-87-9
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 10000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 9400 mg/kg
Test: LC50 - Route: Inhalation Dust - Species: Rat = 0.31 mg/l - Duration: 4h
propylene carbonate - CAS: 108-32-7
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 33520 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause irritation by contact

Sensitizing Properties:

Frequent contact may cause sensitization.

Cancerogenic Effects:

May cause cancer

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

Carcinogenic category 3

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Test carried out on similar product:

Safety Data Sheet

RESFOAM 1K-M

Aquatic toxicity: the preparation is not to be considered toxic to the aquatic environment based on components.

LC50>100mg/l - aquatic species (calculated data following 1999/45/EC Directive).

Biodegradability: not readily biodegradable

diphenylmethanediisocyanate isomers and homologues - CAS: 9016-87-9

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 100 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 83 mg/l - Duration h: 48

propylene carbonate - CAS: 108-32-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 900 mg/l - Duration h: 72

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of not hardened product (EC waste code) : 08 04 09

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

14.1. UN number

UN Number: ==

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

ADR-Upper number: NA

Air (ICAO/IATA): no dangerous good

Sea (IMO/IMDG): no dangerous good

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

Marine pollutant: No

N.A.

14.6. Special precautions for user

N.A.

Safety Data Sheet

RESFOAM 1K-M

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 56

REACH Regulation (1907/2006) ç All. XVII: N.A.

Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement ç IMDG Code ç IATA Regulation

VOC (2004/42/EC) : N.A. g/l

TSCA (USA) : ALL INGREDIENTS LISTED OR EXEMPTED

DSL/NDL (CANADA) : ALL INGREDIENTS LISTED ON DSL OR EXEMPTED

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H351 Suspected of causing cancer.

Safety Data Sheet

RESFOAM 1K-M

H373 May cause damage to organs through prolonged or repeated exposure.
This safety data sheet has been completely updated in compliance to Regulation 2015/830/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the International Air Transport Association (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the International Civil Aviation Organization (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	Substance with a Union workplace exposure limit.
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List