

Safety Data Sheet

SILICAJET ST HP component A

Safety Data Sheet dated 8/2/2017, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SILICAJET ST HP component A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Ogano mineral resin for injection

Uses advised against:

==

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel: +39-02-376731

Fax: +39-02-37673.214

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Danger, Eye Dam. 1, Causes serious eye damage.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard Statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary Statements:

Safety Data Sheet

SILICAJET ST HP component A

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P310 Immediately call a POISON CENTER.

Special Provisions:

None

Contains

Silicic acid, sodium salt

sodium hydroxide; caustic soda

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 75% Silicic acid, sodium salt

CAS: 1344-09-8, EC: 215-687-4

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

>= 2.5% - < 4.99% 2-amino-2-methylpropanol

REACH No.: 01-2119475788-16-0000, Index number: 603-070-00-6, CAS: 124-68-5, EC: 204-709-8

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

4.1/C3 Aquatic Chronic 3 H412

>= 1% - < 2.5% sodium hydroxide; caustic soda

REACH No.: 01-2119457892-27-XXXX, Index number: 011-002-00-6, CAS: 1310-73-2, EC: 215-185-5

⚠ 2.16/1 Met. Corr. 1 H290

⚠ 3.2/1A Skin Corr. 1A H314

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Safety Data Sheet

SILICAJET ST HP component A

Immediately take off all contaminated clothing.

CONSULT A PHYSICIAN IMMEDIATELY.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the skin, the product causes appreciable inflammation, with erythema, scabs, and oedema.

If brought into contact with the eyes, the product causes serious eye injury, such as opacity of the cornea or lesions to the iris.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Limit leakages with earth or sand.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Safety Data Sheet

SILICAJET ST HP component A

- 6.3. Methods and material for containment and cleaning up
Rapidly recover the product, wearing protective clothing.
After the product has been recovered, rinse the area and materials involved with water.
Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.
Retain contaminated washing water and dispose it.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
sodium hydroxide; caustic soda - CAS: 1310-73-2
ACGIH - STEL: Ceiling 2 mg/m³ - Notes: URT, eye, and skin irr
- DNEL Exposure Limit Values
Silicic acid, sodium salt
- CAS: 1344-09-8
Worker Industry: 5.61 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 1.59 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
- sodium hydroxide; caustic soda - CAS: 1310-73-2
Worker Industry: 1 mg/m³ - Consumer: 1 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
- PNEC Exposure Limit Values
Silicic acid, sodium salt
- CAS: 1344-09-8
Target: Microorganisms in sewage treatments - Value: 348 mg/l
- 8.2. Exposure controls
Eye protection:
Safety goggles.
Use close fitting safety goggles, don't use eye lens.

Safety Data Sheet

SILICAJET ST HP component A

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	grey
Odour:	typical
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	>60 °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1,45 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	N.A.
Solubility in oil:	N.A.
Viscosity:	N.A.
Auto-ignition temperature:	N.A.
Explosion limits(by volume):	N.A.
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Safety Data Sheet

SILICAJET ST HP component A

- Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

- Ingestion: Yes
Inhalation: No
Contact: Yes

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

Silicic acid, sodium salt

- CAS: 1344-09-8

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3400 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2.06 g/m³ - Duration: 4h

Test: map1 - Route: Oral - Species: Rat > 159 mg/kg

sodium hydroxide; caustic soda - CAS: 1310-73-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 1350 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rabbit : Positive

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause damage to eyes by contact

Carcinogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity

b) skin corrosion/irritation

Safety Data Sheet

SILICAJET ST HP component A

- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.
 Not available data on the mixture
 Silicic acid, sodium salt

- CAS: 1344-09-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1108 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Daphnia = 1700 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae = 207 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 349 mg/l - Duration h: 96
 sodium hydroxide; caustic soda - CAS: 1310-73-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 45.9 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

UN Number: ==

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

Safety Data Sheet

SILICAJET ST HP component A

Air (ICAO/IATA):	no dangerous good
Sea (IMO/IMDG):	no dangerous good
N.A.	
14.4. Packing group	
N.A.	
14.5. Environmental hazards	
Marine pollutant:	No
N.A.	
14.6. Special precautions for user	
N.A.	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
==	

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) 2015/830
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
- Restrictions related to the product:
 - Restriction 3
 - Restrictions related to the substances contained:
 - No restriction.
- Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"
- Directive 2000/39/CE and s.m.i. (Professional threshold limit)
- Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)
- Directive 105/2003/CE (Seveso III): N.A.
- ADR Agreement – IMDG Code – IATA Regulation
- VOC (2004/42/EC) : N.A. g/l
- Provisions related to directive EU 2012/18 (Seveso III):
- N.A.
- 15.2. Chemical safety assessment
- No

SECTION 16: Other information

- Text of phrases referred to under heading 3:
- H315 Causes skin irritation.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H412 Harmful to aquatic life with long lasting effects.
 - H290 May be corrosive to metals.
 - H314 Causes severe skin burns and eye damage.

Safety Data Sheet

SILICAJET ST HP component A

This safety data sheet has been completely updated in compliance to Regulation 2015/830.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	Substance with a Union workplace exposure limit.
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List
N.A.:	Not available