

Declaration of performance: No. CPR-IT1/0347

1. Unique identification code of the product-type: **TRIBLOCK TMB**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

EPOXYCEMENTITIOUS SELF-LEVELLING TRICOMPONENT COMPOUND FOR SUBSTRATES (CT-C60-F10-A9)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious screed material for internal use in floor construction

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy) www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
System 3 for reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory CSI S.p.A., No. 0497, performed the determination of the class of the reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. 0012IDC\REA\12_3.

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class A2_{fl}-s1	EN 13813:2002
Release of corrosive substances:	CT	
Water permeability:	NPD	
Water vapour permeability:	NPD	
Compressive strength:	C60	
Flexural strength:	F10	
Wear resistance:	A9	
Sound insulation:	NPD	
Sound absorption:	NPD	
Thermal resistance:	NPD	
Chemical resistance:	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**
(name and function)

Milan, 01/07/2013
(place and date of issue)


.....
(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																						
<p style="text-align: center;">12 CPR-IT1/0347 EN 13813:2002 CT-C60-F10-A9 TRIBLOCK TMB <i>Cementitious screed material for internal use in floor construction</i></p> <table><tr><td>Reaction to fire:</td><td>Class A2_{fl}-s1</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C60</td></tr><tr><td>Flexural strength:</td><td>F10</td></tr><tr><td>Wear resistance:</td><td>A9</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class A2 _{fl} -s1	Release of corrosive substances:	CT	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C60	Flexural strength:	F10	Wear resistance:	A9	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class A2 _{fl} -s1																						
Release of corrosive substances:	CT																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C60																						
Flexural strength:	F10																						
Wear resistance:	A9																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						