


## Declaration of performance: No. CPR-IT1/0348

1. Unique identification code of the product-type: **TRIBLOCK TMB**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR  
**SURFACE PROTECTION THREE-COMPONENT EPOXY-CEMENTITIOUS PRODUCT-COATING**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Coating for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity; physical resistance; chemical resistance methods**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy) www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 2+  
System 3 for reaction to fire**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The notified body ICMQ S.p.A., No. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificate of conformity of the factory production control No. 1305-CPD-0616.  
The notified testing laboratory CSI SpA, No. 0497, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. 0012DC\REA\12\_3.**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:



Essential characteristics	Performance	Harmonised technical specification
<b>Abrasion resistance:</b> <b>Water vapour permeability:</b> <b>Capillary absorption and permeability to water:</b> <b>Resistance to thermal shock:</b> <b>Resistance to severe chemical attack:</b>  <b>Crack-bridging ability:</b> <b>Impact resistance:</b> <b>Adhesion strength by pull-off test:</b> <b>Reaction to fire:</b> <b>Dangerous substances:</b>	<b>&lt; 3000 mg</b> <b>Class I</b> <b>&lt; 0,1 kg*m<sup>-2</sup>*h<sup>-0.5</sup></b> <b>≥ 2,0 N/mm<sup>2</sup></b> <b>reduction in hardness</b> <b>Shore D &lt; 50% (Class II)</b> <b>A5 (-10°C), B4,1 (+23°C)</b> <b>Class III</b> <b>≥ 2,0 N/mm<sup>2</sup></b> <b>Class A2<sub>fl</sub>-s1</b> <b>NPD</b>	<b>EN 1504-2:2004</b>

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**  
(name and function)

**Milan, 01/07/2013**  
(place and date of issue)

  
.....  
(signature)

# CE MARKING according to CPR 305/2011 and EN 1504-2:2004

 1305, 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																		
<p style="text-align: center;"><b>12</b> <b>CPR-IT1/0348</b> <b>EN 1504-2:2004</b> <b>TRIBLOCK TMB</b></p> <p style="text-align: center;"><i>Coating for intended use in concrete surface protection by moisture control and increasing resistivity; physical resistance methods</i></p> <table><tr><td>Abrasion resistance:</td><td>&lt; 3000 mg</td></tr><tr><td>Water vapour permeability:</td><td>Class I</td></tr><tr><td>Capillary absorption and permeability to water:</td><td>&lt; 0,1 kg*m<sup>-2</sup>*h<sup>-0,5</sup></td></tr><tr><td>Resistance to thermal shock:</td><td>≥ 2,0 N/mm<sup>2</sup></td></tr><tr><td>Resistance to severe chemical attack:</td><td>reduction in hardness Shore D &lt; 50% (Class II)</td></tr><tr><td>Impact resistance:</td><td>Class III</td></tr><tr><td>Adhesion strength by pull-off test:</td><td>≥ 2,0 N/mm<sup>2</sup></td></tr><tr><td>Reaction to fire:</td><td>Class A2<sub>fl</sub>-s1</td></tr><tr><td>Dangerous substances:</td><td>NPD</td></tr></table>		Abrasion resistance:	< 3000 mg	Water vapour permeability:	Class I	Capillary absorption and permeability to water:	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>	Resistance to thermal shock:	≥ 2,0 N/mm <sup>2</sup>	Resistance to severe chemical attack:	reduction in hardness Shore D < 50% (Class II)	Impact resistance:	Class III	Adhesion strength by pull-off test:	≥ 2,0 N/mm <sup>2</sup>	Reaction to fire:	Class A2 <sub>fl</sub> -s1	Dangerous substances:	NPD
Abrasion resistance:	< 3000 mg																		
Water vapour permeability:	Class I																		
Capillary absorption and permeability to water:	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>																		
Resistance to thermal shock:	≥ 2,0 N/mm <sup>2</sup>																		
Resistance to severe chemical attack:	reduction in hardness Shore D < 50% (Class II)																		
Impact resistance:	Class III																		
Adhesion strength by pull-off test:	≥ 2,0 N/mm <sup>2</sup>																		
Reaction to fire:	Class A2 <sub>fl</sub> -s1																		
Dangerous substances:	NPD																		