

## Declaration of performance: No. CPR-IT1/0461

1. Unique identification code of the product-type: **MAPELASTIC AQUADEFENSE**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

### **DISPERSION LIQUID-APPLIED WATER IMPERMEABLE PRODUCT, (DM O1)**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**all external installations beneath ceramic tiling  
(bonded with a C2 adhesive in accordance with EN 12004)**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 4  
System 3 for waterproofing**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The notified testing laboratory LGAI Technological Center, S.A., N. 0370, carried out the determination of the product-type on the basis of type testing on samples taken by the manufacturer under system 3 and issued the test report N. 14/8067-175.**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:


Essential characteristics	Performance	Harmonized technical specification
<b>Initial tensile adhesion strength:</b> <b>Waterproofing:</b> <b>Crack bridging ability:</b> <ul style="list-style-type: none"><li>– under standard conditions (+23° C)</li><li>– at low temperature (-5° C)</li></ul> <b>Durability for tensile adhesion strength</b> <ul style="list-style-type: none"><li>– after heat ageing:</li><li>– after water contact:</li><li>– after contact with lime water:</li><li>– after freeze-thaw cycles:</li></ul> <b>Release of dangerous substances:</b>	<b>≥ 0,5 N/mm<sup>2</sup></b> <b>No penetration</b>  <b>≥ 0,75 mm</b> <b>≥ 0,75 mm</b>  <b>≥ 0,5 N/mm<sup>2</sup></b> <b>≥ 0,5 N/mm<sup>2</sup></b> <b>≥ 0,5 N/mm<sup>2</sup></b> <b>≥ 0,5 N/mm<sup>2</sup></b> <b>See SDS</b>	<b>EN 14891:2012</b>

- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**  
(name and function)

**Milan, 19/03/2014**  
(place and date of issue)

  
.....  
(signature)

## CE MARKING according to CPR 305/2011 and EN 14891:2012

 0370	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																						
<p style="text-align: center;"><b>14</b> <b>CPR-IT1/0461</b> <b>EN 14891:2012</b> <b>MAPELASTIC AQUADEFENSE</b> <i>Dispersion liquid-applied, water impermeable product DM O1, for all external installations, beneath ceramic tiling (bonded with a C2 adhesive in accordance with EN 12004)</i></p> <table><tr><td>Initial tensile adhesion strength :</td><td>≥ 0,5 N/mm<sup>2</sup></td></tr><tr><td>Waterproofing:</td><td>no penetration</td></tr><tr><td>Crack bridging ability:</td><td></td></tr><tr><td>– under standard conditions (+23° C)</td><td>≥ 0,75 mm</td></tr><tr><td>– at very temperature (-5° C)</td><td>≥ 0,75 mm</td></tr><tr><td>Durability for tensile adhesion strength</td><td></td></tr><tr><td>– after heat ageing:</td><td>≥ 0,5 N/mm<sup>2</sup></td></tr><tr><td>– after water contact:</td><td>≥ 0,5 N/mm<sup>2</sup></td></tr><tr><td>– after contact with lime water:</td><td>≥ 0,5 N/mm<sup>2</sup></td></tr><tr><td>– after freeze-thaw cycles:</td><td>≥ 0,5 N/mm<sup>2</sup></td></tr><tr><td>Release of dangerous substances:</td><td>see SDS</td></tr></table>		Initial tensile adhesion strength :	≥ 0,5 N/mm <sup>2</sup>	Waterproofing:	no penetration	Crack bridging ability:		– under standard conditions (+23° C)	≥ 0,75 mm	– at very temperature (-5° C)	≥ 0,75 mm	Durability for tensile adhesion strength		– after heat ageing:	≥ 0,5 N/mm <sup>2</sup>	– after water contact:	≥ 0,5 N/mm <sup>2</sup>	– after contact with lime water:	≥ 0,5 N/mm <sup>2</sup>	– after freeze-thaw cycles:	≥ 0,5 N/mm <sup>2</sup>	Release of dangerous substances:	see SDS
Initial tensile adhesion strength :	≥ 0,5 N/mm <sup>2</sup>																						
Waterproofing:	no penetration																						
Crack bridging ability:																							
– under standard conditions (+23° C)	≥ 0,75 mm																						
– at very temperature (-5° C)	≥ 0,75 mm																						
Durability for tensile adhesion strength																							
– after heat ageing:	≥ 0,5 N/mm <sup>2</sup>																						
– after water contact:	≥ 0,5 N/mm <sup>2</sup>																						
– after contact with lime water:	≥ 0,5 N/mm <sup>2</sup>																						
– after freeze-thaw cycles:	≥ 0,5 N/mm <sup>2</sup>																						
Release of dangerous substances:	see SDS																						