

DECLARATION OF PERFORMANCE N. CPR-IT1/0436

- 1) Unique identification code of the product-type: **MAPELASTIC TURBO**
- 2) Intended uses: **Liquid-applied, two component, water impermeable product CM O1, for all external installations and swimming pools, beneath ceramic tiling (bonded with a C2 adhesive in accordance with EN 12004)**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 14891:2012**

Notified bodies: **the notified laboratory LGAI TECHNOLOGICAL CENTER, S. A./Applus, N. 0370, carried out the assessment of the performance (Waterproofing) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:


Essential characteristics	Performances
Initial tensile adhesion strength:	≥ 0,5 N/mm²
Waterproofing:	no penetration
Crack bridging ability:	
- under standard conditions (+23°C)	≥ 0,75 mm
- at low temperature (-5°C) (tested with reinforcement)	≥ 0,75 mm
Durability for tensile adhesion strength:	
- after water contact	≥ 0,5 N/mm²
- after heat ageing	≥ 0,5 N/mm²
- after freeze-thaw cycles	≥ 0,5 N/mm²
- after contact with lime water	≥ 0,5 N/mm²
Release of dangerous substances:	see SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 06/07/2015





DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	<i>The intended use description has been amended (the word "normal" has been erased).</i>
--------------------------	-------------------------------------------------------------------------------------------

MAPELASTIC TURBO
CE MARKING
Annex to DoP N. CPR-IT1/0436



 0370	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0436 EN 14891:2012 MAPELASTIC TURBO <i>Liquid-applied, two component, water impermeable product CM O1, for all external installations and swimming pools, beneath ceramic tiling (bonded with a C2 adhesive in accordance with EN 12004)</i>	
Initial tensile adhesion strength:	≥ 0,5 N/mm ²
Waterproofing:	no penetration
Crack bridging ability:	
- under standard conditions (+23°C)	≥ 0,75 mm
- at low temperature (-5°C) (tested with reinforcement)	≥ 0,75 mm
Durability for tensile adhesion strength:	
- after water contact	≥ 0,5 N/mm ²
- after heat ageing	≥ 0,5 N/mm ²
- after freeze-thaw cycles	≥ 0,5 N/mm ²
- after contact with lime water	≥ 0,5 N/mm ²
Release of dangerous substances:	see SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.