

DECLARATION OF PERFORMANCE N. CPR-IT1/0480

- 1) Unique identification code of the product-type: **MAPESIL AC New colors**
(Colors N. 103, 115, 116, 119, 133, 134, 135, 136, 137, 138, 139, 149, 152, 174, 299)
- 2) Intended uses: **silicone sealant for non-structural internal and external use in façade elements and glazing application, also in cold climates, and in sanitary areas**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 15651-1:2012, EN 15651-2:2012, EN 15651-3:2012**

Notified bodies: **The notified laboratory ift Rosenheim GmbH, N.° 0757, carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer**

- 6) Performances declared:

EN 15651-1 F-EXT-INT-CC (CLASS 25LM)
Conditioning: Method A
Substrate: Glass with primer CLEANPRIMER 1226

Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Resistance to flow	≤ 3 mm
– Loss of volume	≤ 10 %
– Tensile properties at maintained extension after immersion in water	Pass
– Secant tensile modulus at -30°C	≤ 0,9 MPa
– Tensile properties at maintained extension at -30°C	Pass
Durability	Pass

EN 15651-2 G-CC (CLASS 20LM)
Conditioning: Method A
Substrate: Glass with primer CLEANPRIMER 1226

Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Resistance to flow	≤ 3 mm
– Loss of volume	≤ 10 %
– Adhesion and cohesion properties after exposure to artificial light	Pass
– Elastic recovery	≥ 60 %
– Secant tensile modulus at -30°C	≤ 0,9 MPa
– Tensile properties at maintained extension at -30°C	Pass

Durability
Pass
EN 15651-3
CLASS XS 1
Conditioning:
Method A
Substrate:
Glass with primer CLEANPRIMER 1226

Essential characteristics	Performances
Reaction to fire	Class E
Release of dangerous substances	See SDS
Water tightness and air tightness:	
– Resistance to flow	≤ 3 mm
– Loss of volume	≤ 10 %
– Tensile properties at maintained extension after immersion in water	Pass
– Microbiological growth	0
Durability	Pass

- 7) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Lorenzo Martino – Corporate Quality Management**

Milan, 17/07/2019



DoP in Pdf format are available in the Mapei website.

Revision 3 notes:	New color 299 + point 7
-------------------	-------------------------

CE marking

<div><div>CE</div><div>0757</div></div>	<div><div><div><div></div><div></div><div></div></div><div>MAPEI</div></div><div>Via Cafiero, 22 - 20158 MILANO – ITALY</div><div>www.mapei.it</div></div>		
<div>14</div> <div>CPR-IT1/0480</div> <div>EN 15651-1 F-EXT-INT-CC</div> <div>EN 15651-2 G-CC</div> <div>EN 15651-3 XS 1</div> <div>MAPESIL AC (New colors)</div> <div>Silicone sealant for non-structural internal and external use in façade elements and glazing applications, also in cold climates, and in sanitary areas</div>			
<div>Conditioning: method A</div> <div>Substrate: Glass with CLEANPRIMER 1226</div>			
	EN 15651-1	EN 15651-2	EN 15651-3
<div>Reaction to fire</div> <div>Release of dangerous substances</div>	Class E See SDS		
<div>Water tightness and air tightness:</div> <div>– Resistance to flow</div> <div>– Loss of volume</div> <div>– Tensile properties at maintained extension after immersion in water</div> <div>– Secant tensile modulus at -30°C</div> <div>– Tensile properties at maintained extension -30°C</div> <div>– Adhesion and cohesion properties after exposure to heat, water and artificial light</div> <div>– Elastic recovery</div> <div>Microbiological growth</div> <div>Durability</div>	<div>≤ 3 mm</div> <div>≤ 10 %</div> <div>Pass</div> <div> </div> <div>≤ 0,9 MPa</div> <div>Pass</div> <div>==</div> <div> </div> <div>==</div> <div>==</div> <div>Pass</div>	<div>≤ 3 mm</div> <div>≤ 10 %</div> <div>==</div> <div> </div> <div>≤ 0,9 MPa</div> <div>Pass</div> <div>Pass</div> <div> </div> <div>≥ 60%</div> <div>==</div> <div>Pass</div>	<div>≤ 3 mm</div> <div>≤ 10 %</div> <div>Pass</div> <div> </div> <div>==</div> <div>==</div> <div>==</div> <div> </div> <div>==</div> <div>0</div> <div>Pass</div>

CE reminder printed on the cartridge



Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.