

DECLARATION OF PERFORMANCE N. CPR-IT1/0494

- 1) Unique identification code of the product-type: **KERAFLEX MAXI S1 ZERO**
- 2) Intended uses: **Improved cementitious adhesive for internal and external tiling on floors and walls**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies: **The notified testing laboratory TUM München N. 1211 carried out the assessment of the performance (other than reaction to fire) on the basis of testing on samples taken by the manufacturer.**

The notified laboratory MPA Dresden GmbH, N. 0767, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

- 6) Performances declared:


Essential characteristics	Performances
Reaction to fire	Class A2-s1,d0 / A2_{fl}-s1
Bond strength, as:	
- Initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for:	
- Tensile adhesion after heat ageing	≥ 1,0 N/mm²
- Tensile adhesion after water immersion	≥ 1,0 N/mm²
- Tensile adhesion after freeze/thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	vedi SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 16/02/2015





DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	First issue
-------------------	-------------

KERAFLEX MAXI S1 ZERO
CE MARKING
Annex to DoP N. CPR-IT1/0494



 1211 , 0767	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
15 CPR-IT1/0494 EN 12004:2007+A1:2012 KERAFLEX MAXI S1 ZERO <i>Improved cementitious adhesive for internal and external tiling on floors and walls</i>	
Reaction to fire	Class A2-s1,d0 / A2fl-s1
Bond strength, as:	
- Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability for:	
- Tensile adhesion after heat ageing	$\geq 1,0 \text{ N/mm}^2$
- Tensile adhesion after water immersion	$\geq 1,0 \text{ N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	vedi SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.