

DECLARATION OF PERFORMANCE N. CPR-IT1/0721

- 1) Unique identification code of the product-type: **MAPEFLOOR I309 CR**
- 2) Intended uses: **Bi-component epoxy resin screed material for use in internal flooring construction**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **The notified laboratory CSI SpA, N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class B_{FL}-s1
Release of corrosive substances:	SR
Water permeability:	Class III
Wear resistance:	AR0,5
Bond strength:	B2,0
Impact resistance:	IR20
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	(Shore D reduction < 50%) CR1: classe II (Change of colour, darker); CR4: classe I; CR5a: classe I; CR10: classe II (Slight loss of gloss); CR11: classe II; CR12: classe II


- 7) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 21/11/2018





.....

DoP in Pdf format are available in the Mapei website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

MAPEFLOOR I309 CR
CE MARKING
Annex to DoP N. CPR-IT1/0721



 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
18 CPR-IT1/0721 EN 13813 MAPEFLOOR I309 CR <i>Bi-component epoxy resin screed material for use in internal flooring construction</i>	
Reaction to fire:	Class B _{FL} -s1
Release of corrosive substances:	SR
Water permeability:	Class III
Wear resistance:	AR0,5
Bond strength:	B2,0
Impact resistance:	IR20
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	(Shore D reduction < 50%) CR1: classe II (Change of colour, darker); CR4: classe I; CR5a: classe I; CR10: classe II (Slight loss of gloss); CR11: classe II; CR12: classe II

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.