

Safety Data Sheet

EPORIP comp.A

Safety Data Sheet dated: 01/04/2021 - version 1

Date of first edition: 01/04/2021



1: Identification

GHS Product Identifier

Mixture identification:

Trade name: EPORIP comp.A

Trade code: 901521

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy adhesive

Uses advised against: Data not available

Supplier's details

Company: Mapei Construction Chemicals Panama S.A.

Via Transistmica, Complejo Bodegas America

Ciudad de Panama, Panama

Responsable: sicurezza@mapei.it

Mapei Construction Chemicals Panama S.A.

Phone: +507 261-9549/9550

Fax: +507 2619549/50 (office hours)

Emergency phone number

Phone: +507 261-9549/9550

2: Hazard identification

Classification of the substance or mixture

Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2A	Causes serious eye irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
Aquatic Chronic 2	Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

GHS label elements, including precautionary statements

Pictograms and Signal Words



Warning

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P261	Avoid breathing mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P391	Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

No other hazards

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

3: Composition/information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of GHS and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥25 - <50 %	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	CAS:25068-38-6 EC:500-033-5 Index:603-074-00-8	Eye Irrit. 2A, H319; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411	01-2119456619-26-xxxx
≥10 - <20 %	1,6-Hexanediol Diglycidyl Ether	CAS:933999-84-9, 16096-31-4 EC:618-939-5	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	01-2119463471-41-0005
≥5 - <10 %	bisphenol F - epoxy resin	CAS:9003-36-5 EC:500-006-8	Skin Irrit. 2, H315; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119454392-40-XXXX

4: First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Unsuitable extinguishing media:

- None in particular.

Special hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: ==
- Oxidizing properties: N.A.

Special protective actions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8: Exposure controls/personal protection

Control parameters

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency	Remark
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	25068-38-6	0.006 mg/l	Fresh Water		
		0.0006 mg/l	Marine water		
		0.0627 mg/kg	Freshwater sediments		
1,6-Hexanediol Diglycidyl Ether	933999-84-9, 16096-31-4	0.00627 mg/kg	Marine water sediments		
		1 mg/l	Microorganisms in sewage treatments		
		0.0115 mg/l	Fresh Water		
		0.283 mg/kg	Freshwater sediments		
		0.00115 mg/l	Marine water		
		0.0283 mg/kg	Marine water sediments		

	0.223 mg/kg	Soil
bisphenol F - epoxy resin 9003-36-5	10 mg/l	Microorganisms in sewage treatments
	0.003 mg/l	Fresh Water
	0.294 mg/kg	Freshwater sediments
	0.0003 mg/l	Marine water
	0.0294 mg/kg	Marine water sediments
	0.237 mg/kg	Soil

Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	25068-38-6	8.3 mg/kg			Human Dermal	Short Term, systemic effects	
		12.25 mg/m3			Human Inhalation	Short Term, systemic effects	
		8.3 mg/kg			Human Dermal	Long Term, systemic effects	
		12.25 mg/m3			Human Inhalation	Long Term, systemic effects	
				3.571 mg/kg	Human Dermal	Short Term, systemic effects	
				0.75 mg/kg	Human Oral	Short Term, systemic effects	
				3.571 mg/kg	Human Dermal	Long Term, systemic effects	
				0.75 mg/kg	Human Oral	Long Term, systemic effects	
1,6-Hexanediol Diglycidyl Ether	933999-84-9, 16096-31-4	2.8 mg/kg			Human Dermal	Long Term, systemic effects	
		4.9 mg/m3			Human Inhalation	Long Term, systemic effects	

Appropriate engineering controls: N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

9: Physical and chemical properties

Physical state: Liquid
Color: Grey
Appearance: liquid
Odour: Characteristic
Odour threshold: N.A.
pH: N.A.
Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.
Flash point: N.A.
Evaporation rate: N.A.
Solid/gas flammability: N.A.
Upper/lower flammability or explosive limits: N.A.
Vapour pressure: 0.01
Vapour density: N.A.
Relative density: 1.60 g/cm³
Solubility in water: Insoluble
Solubility in oil: soluble
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity: 20,000.00 cPs

10: Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

11: Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700)	a) acute toxicity	LD50 Oral Rat > 15000 mg/kg
		LD50 Skin Rabbit > 23000 mg/kg
		LD50 Oral Rat = 11400 mg/kg
	i) STOT-repeated exposure	NOAEL Oral Rat = 50 mg/kg
		NOAEL Skin Rat = 100 mg/kg
1,6-Hexanediol Diglycidyl Ether	a) acute toxicity	LD50 Oral Rat = 2190 mg/kg
		LD50 Skin Rabbit > 4900 mg/kg

i) STOT-repeated exposure

NOAEL Oral = 200 mg/kg

NOAEL Inhalation = 16 mg/m³

bisphenol F - epoxy resin a) acute toxicity

LD50 Oral Rat > 10000 mg/kg

LD50 Skin Rat > 2000 mg/kg

LD50 Oral Rat > 2 g/kg

i) STOT-repeated exposure

NOAEL Oral = 250 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- Toxicological kinetics, metabolism and distribution information
- i) STOT-repeated exposure
- j) aspiration hazard

12: Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	CAS: 25068-38-6 - EINECS: 500-033-5 INDEX: 603-074-00-8	a) Aquatic acute toxicity : LC50 Fish > 2 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia > 1.8 mg/L 48 a) Aquatic acute toxicity : LC50 Algae > 11 mg/L 72 a) Aquatic acute toxicity : LC50 Daphnia = 1.3 mg/L 96 b) Aquatic chronic toxicity : NOEC Daphnia = 0.3 mg/L
1,6-Hexanediol Diglycidyl Ether	CAS: 933999-84-9, 16096-31-4 - EINECS: 618-939-5	a) Aquatic acute toxicity : EC50 Daphnia = 47 mg/L 48 a) Aquatic acute toxicity : LC50 Fish = 30 mg/L 96 a) Aquatic acute toxicity : EC50 Algae = 23.1 mg/L 48 a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 30 mg/L 96h ECHA
bisphenol F - epoxy resin	CAS: 9003-36-5 - EINECS: 500-006-8	a) Aquatic acute toxicity : EC50 Fish = 2.54 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 2.55 mg/L 48

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

No Components with environmental hazard properties found.

13: Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14: Transport information

UN number

3082

UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

Transport hazard class(es)

ADR-Class: 9

IATA-Class: 9

IMDG-Class: 9

Packing group, if applicable

Road and Rail (ADR-RID) :

ADR exempt: No

ADR-Label: 9

ADR-Packing Group: III

ADR-Hazard identification number: NA

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA) :

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Packing group: III

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197

Sea (IMDG) :

IMDG-Packing group: III

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335 969

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-EMS: F-A, S-F

IMDG-MFAG: N/A

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: N.A.

Special precautions for user

N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

These substances, when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids, or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to provisions of ADR, IMDG and IATA DGR.

15: Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Fifth revised edition.

16: Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Insert here further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.